


## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : <b>B43L 13/06</b>	<b>A1</b>	(11) International Publication Number: <b>WO 00/63029</b> (43) International Publication Date: 26 October 2000 (26.10.00)
<p>(21) International Application Number: PCT/US00/10566</p> <p>(22) International Filing Date: 19 April 2000 (19.04.00)</p> <p>(30) Priority Data: 60/130,023 19 April 1999 (19.04.99) US</p> <p>(71) Applicant (for all designated States except US): GRACO INC. [US/US]; 4050 Olson Memorial Highway, Golden Valley, MN 55422 (US).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): SCHROEDER, James [US/US]; 9000 160th Lane, Ramsey, MN 55303 (US).</p> <p>(74) Agent: FARROW, Douglas; Graco Inc., 4050 Olson Memorial Highway, Golden Valley, MN 55422 (US).</p>		<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p><b>Published</b> <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>

(54) Title: SELF-ALIGNING MECHANICAL POINTER



## (57) Abstract

A self-aligning mechanical pointer (10), includes a frame (12) attached to the front of a vehicle (14). A guide wheel (16) rides on a road surface and is rotatably carried by a wheel holder (18). The wheel holder (18) is connected to a swing arm (20), which pivots on frame (12) at point (22). An adjustable linkage member (24) connects swing arm (20) to a second swing arm (26). A guide rod (28) provides a sight means for an operator to align the pointer (10) with an intended target.